



48 to 24 VDC Isolated Converter Model 849HSBP

Step-Down Sealed DC-DC Converter

Design Features

- Wide Range Input Voltage
- High Efficiency Isolated Design - 94%
- Hi Ingress Rating, IP 67
- Adjustable Output Voltage
- Optional Remote Output Voltage Sensing
- Optional Remote On/Off Switching
- Low/High Input Voltage Cutouts
- Electronically Current Limited
- Thermally Protected
- Low No Load Power Consumption
- I/O Bayonet Quick Connection

MODEL NO.		849HSBP
INPUT	NOMINAL INPUT VOLTAGE RANGE	44 to 70 VDC
	MAXIMUM INPUT VOLTAGE RANGE	75 VDC
	INPUT CURRENT WITH LOAD AT 30A; 26.0 Vout	19A with input at 48.0 V
	INPUT INRUSH CURRENT AT FULL LOAD	Limited to 25A
	INPUT CURRENT AT NO LOAD	< 160 mA over entire input and output ranges
OUTPUT	OUTPUT VOLTAGE NOMINAL	26.0 +/- 0.1 VDC (factory adjusted)
	OUTPUT VOLTAGE ADJUSTMENT RANGE	23.5 to 27.0 VDC (internally accessible to user)
	OUTPUT LOAD REGULATION	200 mV (without remote sensing) <30 mV (with remote sensing)
	OUTPUT VOLTAGE REGULATION	< 0.2% with input excursions from 46-56 VDC
	OUTPUT RIPPLE	50 mV RMS at maximum load (measured at 25C)
	MAXIMUM CONTINUOUS OUTPUT POWER	800 W
	POWER SURGE	1000 W
	MAXIMUM LOAD CURRENT	30 ADC, for output voltage setting 23.5-27.0 VDC
PROTECTION	EFFICIENCY	Not less than 94% over entire operating range
	LOW INPUT VOLTAGE SHUTDOWN	40V +/- 1V
	HIGH INPUT VOLTAGE SHUTDOWN	71V +/- 1V
	OVERLOAD SHUTDOWN	Knee current limit starting at 110% of maximum current
	ISOLATION	Input/Output-1800V, Input/Housing-2500V
	OVER TEMPERATURE SHUTDOWN	Via internal thermostat, self resetting
	COOLING	By conduction through base plate and convection
CONNECTIONS	FUSING	Customer accessible by front panel removal
	INPUT/ OUTPUT CONNECTION	Via 9 pin Bayonet connector (see owner's manual)
	REMOTE TURN ON	Via pin H jumpered to -ve Pin I on input connector, may be disabled via internal jumper
	REMOTE SENSE	Via 2 pins on the output connector usage is optional (see user manual)
GENERAL	OPERATING TEMPERATURE RANGE	-40C to 70C, 100% loading
	OPERATING HUMIDITY	100% non condensing
	INGRESS RATING	IP 67
	MOUNTING SLOT CENTERS (in./cm.)	10.0 x 7.3 / 25.4 x 18.5
	DIMENSIONS, (in./cm.) (L x W x H)	15.5 x 8.0 x 2.9 / 39.4 x 20.3 x 7.4
	HOUSING MATERIAL	All Aluminum
WEIGHT, (lb./kg.)		15 /6.8

NOTE: Specifications are subject to change without notice.

Rev 05/12/2025